



Electro Contact Cleaner



FEATURES

- Non-Flammable and Non-Conductive
- Fast Evaporating, No residue
- Quick Penetration
- Ideal for electrical/electronic fine parts
- Removes light greases, oils, dirt, and organic soils
- Safe on plastics
- No ozone depletion potential
- Conforms to CARB, OTC, and LADCO

APPLICATIONS

- Printed Circuits
- Calculators
- Computers
- Digital Equipment
- Electronic Ignitions
- Navigation Equipment
- Switches and Relays
- Radars & Radios

SPECIFICATIONS AND APPROVALS

- Boeing BAC 5750 Rev L.
- Ford Motor Co.
- Inland Steel
- Kimberly-Clark
- MIL-PRF-29608A Type C
- Shell Oil

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
00416	C00416	14 wt oz / 397 g / 301 mL	16 oz	12	14 lbs

PROPERTIES

Appearance/physical state	Gas
Odor	Characteristic
Melting point/freezing point	N/A
Boiling point/range	118.4 °F (48 °C)
Vapor pressure	3103 mm Hg @ 20°C
Partition coefficient	<1
Percent volatile	100%
Flammability limit	N/A
Propellant	HFC-134a
VOC Content	45%
Color	Colorless
Flash point	None (TCC)
Relative density	N/A
Evaporation rate	< 1 (Ethyl Ether = 1)
Vapor density	>1
Auto-ignition temperature	> 482 °F (> 250 °C)
Viscosity	< 3 cSt @ 25°C
Specific Gravity (water=1)	1.38 - 1.4 @ 25°C
Dielectric Strength (ASTM D-877)	22 kV

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to clean. Air dry or wipe with an absorbent cloth for faster drying.

HANDLING

Observe good hygiene practices. Wash hands after handling.

STORAGE

Contains gas under pressure; may explode if heated. Protect from sunlight. Store in a well-ventilated place.

DISPOSAL INFORMATION

Dispose of waste and residues in accordance with local authority requirements.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved