

509 Water St. Bolivar, OH 44612 Phone: 330-455-1181 Fax: 330-455-1191

US Technology Media Technical Data Sheet

Polylite®

Polylite® plastic media is a thermoset Polycarbonate, which has been treated with an anti-static agent, custom manufactured specifically for plastic media blasting. It is available both in MIL-SPEC and Standard grade configurations.

Chemical Nature Inert

Appearance Granular

Color Clear

Hardness Barcol 30-40

MOHS 3.0

Compressive Strength 600-13000 psi psi

Izod impact (1/8" specimen) 0.2-0.4 ft lb/in

Explosibility – Minimum Explosive 0.045 oz/ft³

Ignition Temperature 440°F

Limits per MIL-P-85891A

Chlorine Content Trace

Ash Content 0.5% by wt
Iron Content 0.05% by wt
Specific Gravity 1.30-1.40 gm/cm³

Extract Content 1% by wt

PH 4-8

 $\begin{array}{c} \text{Conductivity} & 100 \text{ mho/cm} \\ \text{H}_2\text{O Absorbtion} & 2\% \text{ by wt} \\ \text{Heavy Particulate} & 0.02\% \text{ by wt} \\ \text{Light Particulate} & 1.0\% \text{ by wt} \\ \end{array}$