5700 Skylab Road Huntington Beach CA 92647 USA Phone: +1 714-899-8100 Fax: +1 714-899-8179 E-mail: airtech@airtechintl.com Website: www.airtechonline.com

Data Sheet

FLASHBREAKER® 2

All purpose pressure sensitive tape

DESCRIPTION

Flashbreaker® 2 tape is a stronger version of Flashbreaker® 1. It can be used anywhere extra strength is needed.

Flashbreaker® tapes are high temperature / high tensile strength polyester films coated with a pressure sensitive silicone adhesive for oven or autoclave cures up to 400 °F (204 °C). The orange Flashbreaker® tapes have high visibility when placed on parts and molds.

Flashbreaker® pressure sensitive tapes are used for multi-purpose functions in metal bond and composites, such as holding down vacuum bagging materials, thermocouple wires, masking-off, chem-milling protection. It offers further protection in chem-milling or acid bath etching. Flashbreaker® tapes remove easily after the cure.

TECHNICAL DATA

Maximum use temperature 400 °F (204 °C)
Carrier type Polyester
Adhesive type Silicone
Color Blue / Orange
Total thickness 0.0033 inch (84

Total thickness 0.0033 inch (84 μ m) Film thickness 0.002 inch (50 μ m) Adhesive thickness 0.0013 inch (33 μ m)

Adhesion Medium Elongation at break 100 %

Shelf life 12 months from date of shipment

Storage conditions 72 °F (22 °C)

SIZES

Width	Length	Packaging
1 inch (2.54 cm)	72 yards (66 m)	36 rolls per case
2 inches (5.08 cm)	72 yards (66 m)	24 rolls per case

NOTES

- > Broken cases available on special order.
- > Other sizes available on special order.

Last updated : 2013-02-12